

FUJIFILM Material Safety Data Sheet

According to 91/155/EC amended by 2001/58/EC

Printing date 25.05.2007

Reviewed on 23.05.2007





1 Identification of Product:

- **Use:** Screen making adhesive
- **Range:** SERIFIX/2
- **Product Code(s):** SFL93
- **Manufacturer/Supplier:** Fujifilm Sericol Limited
Pysons Road, Broadstairs, Kent. CT10 2LE. Tel. +44 (0)1843 866668
- **Supplier:** Mega Electronics Ltd.,
Mega Hs, Grip Ind.Est. Linton,
Cambridge, CB21 4XN
- **Information department:** Product Safety Department. +44 (0)1843 872030
- **Emergency information:** Elaine Campling BSc.(Hons) +44(0)1843 872030

2 Composition/Data on components:

- **Chemical characterization**
- **Description:** Mixture of substances listed below with nonhazardous additions.

- **Dangerous components:**

CAS: 78-93-3 EINECS: 201-159-0	butanone	 Xi,  F; R 11-36-66-67	50-100%
CAS: 141-78-6 EINECS: 205-500-4	ethyl acetate	 Xi,  F; R 11-36-66-67	25-50%

- **Additional information**
For the wording of the listed risk phrases refer to section 16.

3 Hazards identification

- **Hazard description:**



Xi Irritant
F Highly flammable

- **Information pertaining to particular dangers for man and environment**
R 11 Highly flammable.
R 36 Irritating to eyes.
R 67 Vapours may cause drowsiness and dizziness.
- **Classification system**
The classification was made according to the latest editions of the EU-lists, and expanded by company and literature data.
- **Additional information:**
Exposure to component solvent vapours above the occupational exposure limit, stated in Section 8, may result in adverse health effects such as mucous membrane and respiratory system irritation, adverse effects on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.
Organic solvents should not be used for hand cleaning as this may lead to absorption through the skin, skin irritation or dermatitis.

4 First aid measures

- **General information**
Never make an unconscious person vomit or drink fluids.
Immediately remove any clothing soiled by the product.
- **After inhalation**
Supply fresh air. If required, provide artificial respiration. Keep patient warm.
Seek medical treatment in case of complaints.
- **After skin contact** Immediately wash with soap and water and rinse thoroughly.
- **After eye contact**
Rinse open eye for several minutes under running water. Then consult a doctor.

(Contd. on page 2)

Material Safety Data Sheet
According to 91/155/EC amended by 2001/58/EC

Printing date 25.05.2007

Reviewed on 23.05.2007

Range: SERIFIX/2

(Contd. of page 1)

- **After swallowing** Do not induce vomiting; call for medical help immediately.

5 Fire fighting measures

- **Suitable extinguishing agents**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents** Water with full jet.
- **Special hazards caused by the material, its products of combustion or resulting gases:**
In case of fire, the following can be released:
Carbon monoxide (CO)
Under certain fire conditions, traces of other toxic gases cannot be excluded.
- **Protective equipment:** Wear self-contained breathing apparatus.
- **Additional information**
Cool endangered containers with water spray.
Collect contaminated fire fighting water separately. It must not enter the sewage system.

6 Accidental release measures

- **Person-related safety precautions:**
Ensure adequate ventilation
Keep away from ignition sources
Refer to the protective measures stated in Sections 7 and 8. Keep unprotected personnel away.
- **Measures for environmental protection:**
Prevent seepage into sewage system, workpits and cellars.
Do not allow product to reach sewage system or any water course.
Inform respective authorities if seepage into water course or sewage system occurs.
Do not allow to enter sewers/ surface or ground water.
- **Measures for cleaning/collecting:**
Absorb with liquid-binding material (sand, diatomaceous earth, acid binders, universal binders, sawdust).
Dispose of contaminated material as waste according to section 13.

7 Handling and storage

- **Handling**
- **Information for safe handling:**
Store in cool, dry place in tightly sealed containers.
Keep away from heat and direct sunlight.
Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
- **Storage:** Store in accordance with current national regulations.
- **Requirements to be met by storerooms and containers:** Store between 5 - 30°C.
- **Information about storage in one common storage facility:**
Do not store together with alkalis (caustic solutions).
Do not store together with oxidizing and acidic materials.
- **Further information about storage conditions:** None.

8 Exposure controls and personal protection

- **Additional information about design of technical systems:**
Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction.
If these are not sufficient to maintain concentrations of particulates or solvent vapour below the occupational exposure limit stated, then suitable respiratory protection must be worn as a temporary measure and is specified below.

(Contd. on page 3)

Material Safety Data Sheet
According to 91/155/EC amended by 2001/58/EC

Printing date 25.05.2007

Reviewed on 23.05.2007

Range: SERIFIX/2

(Contd. of page 2)

Components with limit values that require monitoring at the workplace:	
78-93-3 butanone	
WEL (Great Britain)	Short-term value: 899 mg/m ³ , 300 ppm Long-term value: 600 mg/m ³ , 200 ppm Sk
IOELV (European Union)	Short-term value: 900 mg/m ³ , 300 ppm Long-term value: 600 mg/m ³ , 200 ppm
141-78-6 ethyl acetate	
WEL (Great Britain)	Short-term value: 400 ppm Long-term value: 200 ppm

Additional information:

The instructions and information provided by the manufacturer of the personal protective equipment on use, storage, maintenance and replacement must always be followed.

General protective and hygienic measures

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Store protective clothing separately.
Avoid contact with the eyes and skin.

Breathing equipment:

In cases of insufficient ventilation use the following respiratory protective device:
CEN: A1 filter.

Protection of hands:

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.
The selection of single or multi-use gloves is dependent upon the level of exposure (nitrile/neoprene gloves will last longer than latex/rubber).
The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance. Always ensure that gloves are free from defects and that they are stored and used correctly.

Type	Latex/Rubber			Nitrile		Neoprene
	Single Use	Multi Use	Heavy Duty (Gauntlets)	Single Use	Multi Use	Heavy Duty (Gauntlets)
Preparation	X	Y	X	X	Y	X
Print Shop						
Solvent Inks	Y	Y	Y	Y	Y	Y
UV Inks	X	X	X	Y	Y	Y
Reclaim	X	X	Y	X	X	Y

Y = recommended X = not recommended

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Penetration time of glove material

The exact break through time has to be obtained from the manufacturer of the protective gloves and must be observed.

Eye protection: Safety glasses**Body protection:** Protective work clothing; disposable overalls are preferable.**COSHH Essentials for Printers Control Guidance Sheet:**

Guidance is provided by the Health and Safety executive (HSE) concerning COSHH (Control of Substances Hazardous to Health) for printers.

See COSHH Essentials for Printers on the HSE website:

www.hse.gov.uk and enter 'COSHH Essentials for printers' in the search bar.

9 Physical and chemical properties:**General Information**

Form:	Fluid
Colour:	According to product specification
Odour:	Characteristic

(Contd. on page 4)

GB

Material Safety Data Sheet
According to 91/155/EC amended by 2001/58/EC

Printing date 25.05.2007

Reviewed on 23.05.2007

Range: SERIFIX/2

(Contd. of page 3)

- **Change in condition**
Melting point/Melting range: undetermined
Boiling point/Boiling range: 76°C
- **Flash point:** -7°C
- **Self igniting:** Product is not selfigniting.
- **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapour mixtures is possible.
- **Vapour pressure at 20°C:** 105.0 hPa
- **Density at 20°C:** 0.89000 g/cm³
- **Water:** Not miscible or difficult to mix
- **Solvent content:**
 - Organic solvents: 83.3 %
 - VOC (EU): 83.40 %
 - Water: 0.0 %

10 Stability and reactivity

- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Dangerous products of decomposition:** No dangerous decomposition products known

11 Toxicological information

- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

78-93-3 butanone

Oral	LD50	3300 mg/kg (rat)
Dermal	LD50	5000 mg/kg (Rabbit)

141-78-6 ethyl acetate

Oral	LD50	4935 mg/kg (Rabbit)
Inhalation	LC50	1600 mg/m ³ (rat)

- **Primary irritant effect:**
- **on the eye:** Irritating effect.

12 Ecological information:

- **General notes:**
There are no data on the preparation itself.
The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and is not classified as dangerous for the environment.

13 Disposal considerations

- **Product:**
- **Recommendation**
Must not be disposed together with household rubbish. Do not allow product to reach sewage system.

- **European waste catalogue**

08 04 09	waste adhesives and sealants containing organic solvents or other dangerous substances
----------	--

- **Waste Hazard Classification:**
H3A - Highly Flammable
H4 - Irritant
- **Recommendation:**
Dispose of product according to official regulations.

(Contd. on page 5)

Material Safety Data Sheet
According to 91/155/EC amended by 2001/58/EC

Printing date 25.05.2007

Reviewed on 23.05.2007

Range: SERIFIX/2

(Contd. of page 4)

Also see Section 16 'Other Information'

14 Transport information

· Land transport ADR/RID (cross-border)



- ADR/RID class: 3 Flammable liquids.
- Danger code (Kemler): 30
- UN-Number: 1210
- Packaging group: II
- Label: 3
- Description of goods: 1210 PRINTING INK RELATED MATERIAL, special provision 640D

· Maritime transport IMDG:



- IMDG Class: 3
- UN Number: 1210
- Label: 3
- Packaging group: II
- EMS Number: F-E,S-D
- Marine pollutant: No
- Proper shipping name: PRINTING INK RELATED MATERIAL

· Air transport ICAO-TI and IATA-DGR:



- ICAO/IATA Class: 3
- UN/ID Number: 1210
- Label: 3
- Packaging group: II
- Proper shipping name: PRINTING INK RELATED MATERIAL

15 Regulations

· Markings according to EU guidelines:

The product has been classified and marked in accordance with EU Directives on Hazardous Materials

· Code letter and hazard designation of product:

Xi Irritant
F Highly flammable

· Risk phrases:

11 Highly flammable.
36 Irritating to eyes.
67 Vapours may cause drowsiness and dizziness.

· Safety phrases:

16 Keep away from sources of ignition - No smoking.
39 Wear eye/face protection.
51 Use only in well-ventilated areas.

GB

(Contd. on page 6)

Material Safety Data Sheet
According to 91/155/EC amended by 2001/58/EC

Printing date 25.05.2007

Reviewed on 23.05.2007

Range: **SERIFIX/2**

(Contd. of page 5)

16 Other information:

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

*For UK Only; disposal can be arranged by Environmental Services,
Telephone Number: (01843) 872080
Fax Number: (01843) 872068*

· Relevant R-phrases

11 Highly flammable.

36 Irritating to eyes.

66 Repeated exposure may cause skin dryness or cracking.

67 Vapours may cause drowsiness and dizziness.

· Recommended restriction of use

The product should not be used for any purpose other than that specified in Section 1.

· Department issuing MSDS: *Technical Administration - Fujifilm Sericol UK Limited*

· Contact: *Elaine Campling BSc.(Hons) - Product Safety Manager*

GB