

RBM 300 BRUSHING MACHINE

PART NUMBER: 500-1 10



A professional brushing machine designed for use in small series production and laboratories.

USERS MANUAL



MEGA ELECTRONICS LIMITED.

Mega House, Grip Industrial Estate, Linton, Cambridge. England. CB21 4XN
Telephone: +44 (0) 1223 893900 Fax: +44 (0) 1223 893894
email: sales@megauk.com web: www.megauk.com

The Bungard RBM 300 is a small wet processing brushing machine for professionally cleaning and roughening of PCB's.

It is suitable for all cleaning steps in the course of PCB production.

Features:

- The RBM 300 has an oscillating brush with quick change holder.
- Brush, dryer, oscillation, and transport can be switched on and off separately.
- In addition the oscillation frequency of the brush and the speed of the conveyor is step less adjustable.
- The double side parallel adjustment of the brush is of great importance, because in contrast to the widely used single side brush adjustments only the mutual parallel adjustment will enable a long lasting uniform brushing result.
- The machine can be equipped with various brushes so that finishing PCB's before laminating is possible as well as slight de-burring after drilling can be fulfilled.
- The usable width is 300 mm.
- In spite of its small size the RBM 300 comes with a complete squeeze off and hot air drying zone behind the wet processing brush zone.
- The integrated frequency converter allows the machine to work worldwide with all power supply systems and enables smooth start and enhanced motor protection.
- Being simply a table size model the RBM300 lacks only the integrated rinse water treatment of its bigger sister, the RBM402. A separate rinse water treatment tank is available as an option.

TECHNICAL DATA

Power supply:	110 - 230 V~, 50-60 Hz	Board Sizes (minimum)	80 X 160mm
Board Thickness (rigid boards only)	0.3 – 3mm	Oscillation Stroke	10mm
Working width:	300 mm	Oscillation frequency	ca. 10 – 110 H / min
Conveyor speed	ca.0,2 – 2 m/min	Brushing roller Stroke	max. 20mm
Water supply connection	Ø 19 mm	In feed per turn of hand wheel	ca. 1 mm
Brushing roller length	310mm	Rinsing system water inlet	20mm
Brushing roller outside dia.	89 - 91mm	Rinsing system water outlet	32mm
Brush roller inner Dia.	35mm	Rinsing system pressure max.	1.5bar
Brush Speed	1360 r.p.m.		
Weight:	80 kg		
External dimensions			
	length : 760mm		
	width : 590mm		
	height : 415mm		

Technical details are subject to change without notice

Please apply the general safety rules for working with electrical machines. Do not run the machine in corroding, humid, dusty, extremely hot or explosive atmosphere.

If you do run the machine in an atmosphere as described above be aware that this happens on your own risk and responsibility.

The operator has to provide appropriate safety precautions and equipment. We explicitly exclude any warranty for damages resulting from running the machine in an unsuitable atmosphere as described above.

Important: When changing the brush you must pay attention to the correct rotating direction of the brush to avoid damage.

For security reason, brushing rollers can only be activated if top cover is closed.

Attention: Do not start brush motor when brush is under load.

Do not touch heating elements and tubes.

Danger of burns!!

SET-UP

Check packing and machine for transport damages.

If such appear inform your transport agent, your local dealer immediately and us and comment on the damage on the Delivery Note accordingly.

Unpack the machine at its final location. The RBM 300 requires a flat, level surfaced table to enable easy changing of the brushes later on. We recommend that you do not place the machine directly next to a wall.

For easy transport the hand wheel for adjusting the brush is not yet mounted. Please mount this wheel first and tighten it with the Allen Key screw. The power connection must be in accordance to the details on the information plate and your local standards.



The RBM 300 is equipped with a frequency converter, which makes the machine suitable for all power systems worldwide and enables a smooth start function as well as a motor protection against overload. The machine is delivered with power cord and safety plug. The water supply for RBM 300 requires a stop valve and a pressure reducer (maximum pressure for rinsing system: 1,5 bar). The discharge must be trapped but has to avoid backdraughts. Please consider your local environmental laws. In many countries you may not directly pour the rinse water into the drain but rather pre-set a filtration system.

Power Connection

Power connection has to be done according to machine requirements (see nameplate) in combination with your local standards. Cable colours are as follows:

Brown = live, Blue = Neutral, Yellow/Green = Earth

After the machine is installed correctly and according to local regulation, check the machine functions

INSTRUCTIONS

As an option we offer a closed cycle rinsing module, which filters the rinsing water and pumps it back into the machine. After machine is installed correctly and according to local regulations, check machine functions. Check that all switches (for brush, dryer, conveyor, oscillation and mains) are off.

Check if brushing roller is fixed correctly. If not, fix it hand-tight with the included socket spanner (wrench / Item no. SW41).

See details in chapter 6.1 exchange of brushing roller. Now switch on mains. The lamp should be lit. Distance of brushing roller is pre-set to maximum. Setting may be modified by means of the hand wheel. Feed motion of brushing roller is clockwise. 1 mm in-feed increment per. 360° turn of hand wheel.

For security reason, brushing rollers can only be activated if top cover is closed. Turn on brush. Attention: To avoid damage to the motor and extreme mechanical wear do not start the brush under load. Switch on oscillation. Check that oscillation speed may be varied with potentiometer. Switch on conveyor and check if rollers are turning correctly and speed may be varied with the potentiometer. Switch on dryer. Attention, do not touch heating elements and tubes. Heating-up time has to be approx. 3 min.



OPERATION OF THE MACHINE

Surface quality

The RBM is equipped with medium fine brushing rollers for deoxidisation and soft burring. The surface quality is a function of different parameters such as pressure, oscillation, conveyor speed, material quality and requirement of the job (deoxidisation, polishing, burring). Optimised pre-setting has to be found by individual tests.

Pre-setting of RBM

Turn on the main switch. Adjust distance of brushing roller to maximum possible values. Turn on brushing rollers and oscillation. Adjust pressure according to board thickness. For pressure adjustment we recommend a PCB of 200 mm and minimal length of 250mm. Enter board and modify the distance of brushing roller so that pressure is sufficient to clean the surface softly. You can hear the motor load increasing as soon as the brush touches the board.

Normally it is sufficient for PCB processing to work with low pressure to remove oxides and to have a good base for PTH or photo laminating. Only deep scratches in the PCB surface require higher pressure and if necessary treat with more than one processing.

Drying

The dryer consists of a mechanical and a hot-air drying compartment. Drying efficiency is best at low conveyor speed.

Please note that important for good results is that the drying clothes are in a good condition. They have to be exchanged from time to time. Moist clothes work better than totally dry ones. If the PCB leaves the machine completely dry you have to reduce the speed to minimum. You can post-dry the board by putting it on the heat grid sheet.

MAINTENANCE

6.1. Exchange of brushing roller

Lift brushing roller by turning the hand wheel counter clockwise. Demount the grey capon the machine's side (Fig.1). Notice the exact position of all parts as you disassemble. This will simplify the reassembly to a great extent. Open top cover of the machine.

Block the brushing roller manually and loosen full floating axle clockwise (left-handed thread Fig 1) until you can pull it off.

Fig 2 & 3). Take out brushing roller and dismount the shaft nut with special 41 mm wrench

Fig 4). Insert shaft into new brushing roller and fix it. Attention: take care of the sense of rotation, marked on the brush. Insert complete unit into the machine. Insert full floating axle, fix it hand-tight by turning counter clockwise. Close the top cover. Grind brushing roller if necessary.



fig 1



fig 2



fig 3



fig 4

6.2 Exchange of drying clothes

Clothes are changed upon need. Switch off dryer and let it cool down. Demount the heat grid sheet by loosening the 4 Allen key screws.

Dismount upper dryer cover and squeeze roller. Remove old drying clothes and clean rollers. Fix new double-sided tape on the lower roller. Put tissue on adhesive tape, use the conveyor system to roll it up.

Apply double side adhesive tape to upper roller. Cover upper roller with cloth. Roll up cloth and insert upper squeeze roller into machine.

6.3. Bearings

All friction bearings have to be oiled. Worm gear pair of brushing roller lifts must be greased.

Attention: Full floating axle of oscillation system is fitted with silicon based sliding bearings that should not be greased or oiled.

6.4. Grinding in of brushing rollers

New and/or worn out brushing rollers have to be ground by use of the included rubbing plate. Insert rubbing plate (rough side top) so that plate is fixed by one pair of press rollers each left and right to the brush. Stop conveyor. Activate rinsing. Switch on brush rotation and oscillation. Feed brushing rollers by turning hand wheel clockwise until you hear the motor load increasing. Repeat until the brush surface is levelled over the entire working width. Turn on conveyor and drive out rubbing plate.



Your brushing machine is ready for use now!

Guarantee

All machines are submitted before distribution to examination on function and continuous operation firmness. On the machine we grant a work warranty of 12 months to our customers starting from purchase date on accuracy in material and processing. We warrant at our choice by exchange of incorrect parts or by repair of the machine in our house. Old parts change into our possession.

Warranty

All parts subjected to wear are excluded from this warranty. Non observance of this manual shall void all warranty claims. We cannot accept subsequent claims from damage or destruction of work pieces worked on in the machine, because we have no knowledge or control over the operating conditions at your site. This is valid in a general manner also for requirements from damage to articles, buildings and persons as well as the environment. We do not warrant that the function of the machine will meet the customer's requirements or that the operation of the machine will to this regard be error free. In no event will we be liable to the customer for any incidental, consequential, or indirect damages of any kind, including loss of profit and prosecution for environmental pollution, even if we could have been aware of the possibility of such damages. All information was arranged with great care. We reserve ourselves however mistake and technical changes without previous announcement. Running the machine in corroding, humid, dusty, extremely hot or explosive atmosphere happens at the operator's own risk and responsibility. We explicitly exclude any warranty for damages resulting from running the machine in in corroding, humid, dusty, extremely hot or explosive atmosphere



MEGA ELECTRONICS LIMITED.,

Mega House, Grip Industrial Estate,
Linton, Cambridge. CB21 4XN

Telephone: +44 (0) 1223 893900 Fax No. +44 (0) 1223 893894

email: sales@megauk.com Web: www.megauk.com